

315/80R22.5-20PR 12.00R24-20PR

ER816



ALL STEEL RADIAL TYRE

KEY SPECIFICATIONS:

Tyre size: 315/80R22.5-20PR, 12.00R24-20PR

Pattern: ER816

Certificates: CCC, DOT, ECE, GCC

SPECIAL FEATURES:

Versatile pattern provides good traction and stability for various road surface. Shoulder desgin minimizes heat buildup. Suitable for all wheel position of truck. National highways and Regional roads as well as on-off road condition.

A SAFETY WARNING

Serious Injury or Death may result from

Follow owner's manual or vehicle tyre placard. Explosion of tyre I rim assembly due to improper mounting. Only specially trained persons should mount tyres.

Tyre Mounting Safety Precaution

Follow RMA installation safety procedures for mounting and inflating tyres. Never mount tyre on a cracked, ben rusted or otherwise damaged rim. Never put a flammable substance into a tyre / rim assembly



FALES GRAND INT'L CO. LTD.





ALL STEEL RADIAL TYRE

NEY SPECIFICATIONS:

Tyre size: 12.00R24-20PR

Pattern: ER580

Certificates: CCC, DOT, ECE, GCC

> SPECIAL FEATURES:

Mixed rib pattern. Good grip grasping capability. Sideslip resistance. Pitch pattern designed. Low noise Suitable for all kinds of roads.

A SAFETY WARNING

Serious Injury or Death may result from

Follow owner's manual or vehicle tyre placard. Explosion of tyre
/ rim assembly due to improper mounting. Only specially trained
persons should mount tyres

Tyre Mounting Safety Precaution:

Follow RMA installation safety procedures for mounting and inflating tyres. Never mount tyre on a cracked, ben rusted or otherwise damaged rim. Never put a flammable of the control of th



FALES GRAND INT'L CO. LTD.



315/80R22.5-20PR 295/80R22.5-20PR

ER829



ALL STEEL RADIAL TYRE

NEY SPECIFICATIONS:

Tyre size: 315/80R22.5-20PR, 295/80R22.5-20PR

Pattern: ER829

Certificates: CCC, DOT, ECE, GCC

> SPECIAL FEATURES:

Block pattern designed for drive position providing first-class performance on grip, tractions and stability. Wider tread width with inter-linked blocks for longer mileage and inner wear. Suitable for drive position of truck. Highways and national roads.



Serious Injury or Death may result from

Follow owner's manual or vehicle tyre placard. Explosion of tyre / rim assembly due to improper mounting. Only specially trained persons should mount tyres.

Tyre Mounting Safety Precaution

Follow RMA installation safety procedures for mounting and inflating tyres. Never mount tyre on a cracked, ben rusted or otherwise damaged rim. Never put a flammable substance into a tyre / rim assembly



FALES GRAND INT'L CO. LTD.





ALL STEEL RADIAL TYRE

NEY SPECIFICATIONS:

Tyre size: 315/80R22.5-20PR

Pattern: ER817

Certificates: CCC, DOT, ECE, GCC

> SPECIAL FEATURES:

With extra aggressive passing performance suitable for both civil and military use. Providing heavy load capability and excellent anti-impact performanceDownload more information about this product

A SAFETY WARNING

Serious Injury or Death may result from

Tyre failure due to under inflation and for overloading Follow owner's manual or vehicle tyre placard. Explosion of tyre / rim assembly due to improper mounting. Only specially trained p.e.r.s.o.n.s.s.hould mount tyres.

Tyre Mounting Safety Precaution:

Follow RMA installation safety procedures for mounting and inflating tyres. Never mount tyre on a cracked, beningsted or otherwise damaged rim. Never put a flammable state of the safety of the safet



FALES GRAND INT'L CO. LTD.