



**PT 766**

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD(kg)	
					S	D
385/65R22.5	20	160	K	11.75	4500	-



**PT 880**

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD(kg)	
					S	D
1200R24	20	160/157	K	8.50	4500	4125



**PT 899**

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD(kg)	
					S	D
315/80R22.5	20	156/152	L	9.00	4000	3550

**POWERGT**

**FALES GRAND proudly adding its fully owned tyre brand 'POWER GT'.**

The brand is specially launched in TBR (Truck-Bus Radial) range with national and international certificates including ISO9001:2008, DOT, etc. and attempting to get more international quality certification to satisfy customer requirements round the globe.

We are grateful for the support from all friendly partners and we are looking forward to establish long term business relationship. We will assure our quality products with excellent services at all times.



**HEAD OFFICE:**  
**FALES GRAND**  
**GENERAL TRADING LLC**  
 Add.: P. O. Box 171018,  
 Al Maktoum Hospital Road,  
 Deira, Dubai, United Arab Emirates.  
 Tel.: + 971 4 2288441 Fax: +971 4 2287876

**REGIONAL OFFICE:**  
**QINGDAO FALES GRAND**  
**INTERNATIONAL CO. LTD.**  
 Add.: 1003, Suite B, Ruina Condo,  
 No. 8, Haimen Road,  
 Beside Shangri-la, Qingdao, P.R. China.  
 Tel.: +86 532 83861223 Fax: +86 532 83862110



**POWERGT**

**RADIAL**



**TBR**  
**TRUCKBUSRADIAL**  
**TYRE**



**PT 520**

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD <sub>(KG)</sub>	
					S	D

315/80R22.5 20 156/150 L 9.00 4000 3350



**PT 580**

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD <sub>(KG)</sub>	
					S	D

1200R24 20 160/157 K 8.50 4500 4125



**PT 589**

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD <sub>(KG)</sub>	
					S	D

315/80R22.5 20 156/152 L 9.00 4000 3550



**PT 716**

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD <sub>(KG)</sub>	
					S	D

825R16	16	128/124	M	6.50	1800	1600
900R20	16	144/142	K	7.00	2800	2650
1000R20	18	149/146	J	7.50	3250	3000
1100R20	18	152/149	J	8.00	3550	3250
1200R20	18	154/149	K	8.50	3790	3270
1200R24	20	160/157	K	8.50	4500	4125
315/80R22.5	20	156/152	L	9.00	4000	3550
13R22.5	20	156/152	L	9.75	4000	3550



**PT 721**

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD <sub>(KG)</sub>	
					S	D

1200R24 20 160/157 K 8.50 4500 4125



**PT 758**

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD <sub>(KG)</sub>	
					S	D

315/80R22.5 20 156/152 L 9.00 4000 3550