



A685

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD(KG)	
					S	D
12.00R24	20	160/157	K	8.5	4500/4125	

A690

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD(KG)	
					S	D
12.00R24	24	160/157	K	8.5	4500/4125	



Fales Grand



Fales Grand General Trading L.L.C.
 P. O. Box 171018, Al Maktoum Hospital Rd., Deira, Dubai, U. A. E.
 Tel : +971 4 2288441 Fax : +971 4 2287876

Qingdao Fales Grand International Co. Ltd.
 1003, Suite B, Ruina Condo, No. 8 Haimen Rd., Qingdao, P.R.C.
 Tel : +86 532 83861223 Fax : +86 532 83862110

Enquiry : sales@falesgrand.com
 More details : www.falesgrand.com



A-ONE



A-ONE

ALL STEEL **TBR**
 TRUCK BUS RADIAL
 TYRE





A660

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD(kg)	
					S	D
7.00R16	14	118/114	K	5.50F	1320/1180	
7.50R16	14	122/118	K	6.00G	1500/1320	
8.25R16	16	128/124	K	6.50H	1800/1600	
8.25R20	16	139/137	K	6.5	2430/2300	
9.00R20	16	144/142	K	7.0	2800/2650	
10.00R20	18	149/146	K	7.5	3250/3000	
11.00R20	18	152/149	K	8.0	3550/3250	
12.00R20	20	154/151	K	8.5	3750/3450	
12.00R24	20	160/157	K	8.5	4500/4125	
12R22.5	18	152/149	M	9.0	3550/3275	
13R22.5	18	154/151	L	9.75	3750/3450	
315/80R22.5	18	154/151	M	9.0	3750/3450	
315/80R22.5	20	157/153	L	9.0	4125/3650	

A602

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD(kg)	
					S	D
7.50R16	14	122/118	K	6.00G	1500/1320	
9.5R17.5	18	143/141	M	6.75	2725/2575	



A608

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD(kg)	
					S	D
10.00R20	18	149/146	K	7.5	3250/3000	



A676

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD(kg)	
					S	D
9.00R20	16	144/142	K	7.0	2800/2650	
10.00R20	18	149/146	K	7.5	3250/3000	
11.00R20	18	152/149	K	8.0	3550/3250	
12.00R20	20	154/151	K	8.5	3750/3450	



A678

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD(kg)	
					S	D
12.00R20	20	154/151	K	8.5	3750/3450	

A680

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD(kg)	
					S	D
12.00R24	24	160/157	K	8.5	4500/4125	



A682

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD(kg)	
					S	D
10.00R20	18	149/146	K	7.5	3250/3000	
11.00R20	18	152/149	K	8.0	3550/3250	
12.00R20	20	154/151	K	8.5	3750/3450	





A658



SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD(kg)	
					S	D
11.00R20	18	152/149	K	8.0	3550/3250	



A609



SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD(kg)	
					S	D
315/80R22.5	20	156/150	M+S	9.0	4000/3350	

A670

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD(kg)	
					S	D
9.00R20	16	144/142	K	7.0	2800/2650	
10.00R20	18	149/146	K	7.5	3250/3000	
11.00R20	18	152/149	K	8.0	3550/3250	
12.00R20	20	154/151	K	8.5	3750/3450	



A610

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD(kg)	
					S	D
12.00R24	20	160/157	K	8.5	4500/4125	
11.00R20	18	152/149	K	8.0	3550/3250	
12.00R20	20	154/151	K	8.5	3750/3450	
7.50R16	14	122/118	K	6.00G	1500/1320	
8.25R16	16	128/124	K	6.50H	1800/1600	



A670+



SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD(kg)	
					S	D
12.00R24	24	160/157	K	8.5	4500/4125	



A612



SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD(kg)	
					S	D
11R22.5	16	146/143	M	8.25	3000/2725	
12R22.5	18	152/149	M	9.0	3550/3275	
295/80R22.5	18	152/149	M	9.0	3550/3250	

A675

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD(kg)	
					S	D
11.00R20	18	152/149	M	8.0	3550/3250	
12.00R20	20	154/151	M	8.5	3750/3450	



A614

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD(kg)	
					S	D
12R22.5	18	152/149	M	9.0	3550/3250	





A615

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD _(KG)	
					S	D
11R22.5	16	146/143	M	8.25	3000/2725	
12R22.5	18	152/149	M	9.0	3550/3275	
315/80R22.5	18	154/151	M	9.0	3750/3450	
315/80R22.5	20	157/153	L	9.0	4125/3650	
295/80R22.5	18	152/149	M	9.0	3550/3250	

A616

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD _(KG)	
					S	D
315/80R22.5	18	154/151	M	9.0	3750/3450	
315/80R22.5	20	157/153	L	9.0	4125/3650	



A618

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD _(KG)	
					S	D
315/80R22.5	18	154/151	M	9.0	3750/3450	
315/80R22.5	20	157/153	L	9.0	4125/3650	



A620

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD _(KG)	
					S	D
315/80R22.5	20	157/153	L	9.0	4125/3650	



A628

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD _(KG)	
					S	D
11.00R20	18	152/149	K	8.0	3550/3250	



A645

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD _(KG)	
					S	D
12R22.5	18	152/149	M	9.0	3550/3275	



A648

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD _(KG)
					S
385/65R22.5	20	160	K	11.75	4500



A650

SIZE	PR	LOAD INDEX	SPEED SYMBOL	STANDARD RIM	MAX LOAD _(KG)	
					S	D
11.00R20	18	152/149	K	8.0	3550/3250	
12R22.5	18	152/149	K	9.0	3550/3250	

